

# Anton LED Pendant ANP Series

## **Features**

This modern double layer drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft.

# Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

#### **Finish**

Stamped metal components are paintable white baked gloss enamel.

#### Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic. Available in Jute and Linen White. Matte white acrylic bottom diffuser.

#### Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120VAC.

# **LED**

Integrated LED modules capable of producing:

12" - 15W - 1400 source lumens

15" - 24W - 2400 source lumens

19" - 35W - 3200 source lumens

Adjustable Choice 3000K, 3500K, 4000K (CCT).

Rated for 50,000 Hrs., 90 CRI


# Certification

cETLus listed for indoor damp locations \*Title 24/JA8 Compliant

## Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


Specifications and dimensions subject to change without notice.











# Ordering Information:

			Source			
Satin Nickel/Jute	Satin Nickel/Linen White	LED	Lumens	Adjustable CCT	DIA.	Н
ANP1214LAJUDSN-JT	*ANP1214LAJUDSN-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANP1524LAJUDSN-JT	*ANP1524LAJUDSN-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANP1932LAJUDSN-JT	*ANP1932LAJUDSN-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"